EGK-LW22PLG



LoRaWAN® energy meter plug with I/O

The EGK-LW22PLG is a compact C-class LoRaWAN® meter that can monitor and switch a 230Vac - 16A Load (active, reactive and apparent energy, Class 0.2s), equipped with a rechargeable battery for mains outage detection, with configurable default power-on status.



Digital Digital Inputs Outputs

Thresholds



Battery for

power failure

alert

٩

ON/OFF

Bluetooth

Smart

- Programmable power thresholds for **real time** event.
- Internal battery for power failure alarm

Customizable

- **Programmable thresholds** via app or remote
- Button can be deactivated
 Configurable output status at power on

Simple

Easy installation and set-up



Multimeasures

Cumulative active, reactive and apparent energy, istantaneous active, reactive and apparent power, istantaneous voltage, current and period and running time

LASS 1.2S High accuracy Measurement

Bluetooth

Bluetooth interface for **configuration** and **diagnostic**

EGK-LW22PLG

LoRaWAN® energy meter plug with I/O

Applications

- Energy metering
- Powerline quality measure
- Remote load control
- Mains blackout alarm
- Machinery maintenance

Specifications

- CPU ARM Cortex M4
- Class C LoRaWAN® 1.0.2 , EU868
- OTAA/ABP activation
- Metering and switch of a 230Vac 16A Load (active, reactive and apparent energy, Class 0.2s)
- Error on energy measurement ±0.2% @100% load
- Configurable default power-on status
- Instantaneous reading of active, reactive and apparent power, voltage and current
- Power supply from line, 230 VAC, 50 Hz
- Bicolor led (green, blue), for output and LoRaWAN® status
- Overload protection
- Rechargeable battery for powerline outage detection

- Embedded antenna
- Pushbotton for forcing transmission or re-join, ON/OFF (lockable),
- Time interval based or thresholds based uplink
- Transmission @868 MHz, 14dBm max.
- BLE 5.0 interface for configuration, data reading and FW upgrade
- Remote configuration
- Storage temperature -10°C ÷ +70°C
- Working temperature -10°C ÷ +50°C
- Dimensions: 110x62x35mm
- Protection grade: IP20
- Weight: 140g



EGK-LW22PLG official web page:



enginko

Enginko^e SRL Amministrazione e Commerciale • Via Roma 3, 28060 Sozzago (NO) – Italy • T +39 0321 1593088 Enginko^e SRL Ricerca / Sviluppo e Produzione • Via Lago di Bolsena 27, 36015 Schio (VI) – Italy • T +39 0445 576734 www.enginko.com

AdriNet d.o.o. - Jaruščica 9a, 10000 Zagreb, Croatia - Tel: +385 1 888 6884 For more information, contact us: sales@adrinet.hr - www.adrinet.hr