

Ambient transmitter LoRa / LoRaWAN

TX temperature and humidity



COMPACT DESIGN

EASY TO INSTALL

VERY LONG RANGE RADIO

REPLACEABLE BATTERY

FREESTANDING OR WALL MOUNTED

VERY HIGH BATTERY LIFE > 20 YEARS

SPECIFICATIONS

Enclosure and IP rating	ABS IP 40
Dimensions (l x w x h)	99 x 85 x 32 mm
Mounting	Wall
Radio antenna	Embedded
Types of sensors	Embedded temperature and humidity sensors
Sensor temperature range	- 40 / + 125 °C
Temperature sensor accuracy	+/- 0,2°C
Humidity sensor resolution	+ / - 2% rH
TX working temperature	- 20 / + 55°C
Power supply	Replaceable 3.6 V C size Lithium battery - Low battery alert
Radio frequency band Protocol	868 MHz bidirectional LoRa – LoRaWAN
Output power	25mW (14 dBm)
Datalogging	Option
Battery autonomy / Periodicity	LoRa mode : 12 years with 5 min periodicity / LoRaWAN : >15 years with 15 min periodicity. Configurable periodicity
Configuration / Installation	Via radio - LoRa mode : Embedded IP server - Mode change via jumper (provided)
ID	DEV EUI in LoRaWAN mode ; LoRa ID in private mode
LED	3 LEDs
Certification	CE
Ordering code	TX T&H AMB 600-021

DS EN -600-021-a